



## PRODUCT BULLETIN

---

# **ELDORADO ALK-660**

## AEROSPACE EQUIPMENT CLEANER

**ELDORADO ALK-660** is a biodegradable, water-dilutable, environmentally safe cleaning compound used to remove oil, exhaust tract film, and traffic film from aircraft exteriors. It may also be used for cleaning cabin and baggage areas of aircraft interiors, as well as gas trucks, ground service units, and freight-handling equipment. It is also intended to be used to clean surfaces prior to recoating with sealant, primers, and paint systems. **ALK-660** is designed for rapid biodegradation and efficient oil separation in wastewater treatment facilities.

### PROPERTIES

1. Nonflammable; pH 9.
2. Safe on plastic transparencies, paint, and electrical insulation.
3. Safe on aluminum, magnesium, ferrous alloys, and high-strength steel.
4. Approved by or conforms to: MIL-PRF-87937D, Type II

### USE

For spot cleaning or heavy-duty cleaning, such as oily soils or exhaust tracts, mix 1 part **ALK-660** with 5 parts' water. Apply by spray, mop, or brush. Allow 5-10 minutes for penetration, then agitate with a brush, and rinse thoroughly with water.

For normal aircraft/equipment cleaning, mix 1 part **ALK-660** with 10 parts of water. For light-duty cleaning, mix 1 part **ALK-660** with 18 parts' water. Apply by spray or foam-generating equipment and allow to remain on the surface 5-10 minutes. Agitate with a brush or mop, and rinse thoroughly with water.

For cleaning aircraft interior surfaces, mix 1 part **ALK-660** with 20 parts of water. Apply to surface being cleaned, with a rag or spray bottle. Pick up loosened dirt and **ALK-660** solution with a clean, dry rag. No other rinse is necessary. This procedure is used on nonporous surfaces, such as metal, wood, and vinyl plastics.

### PRECAUTIONS

Prolonged skin contact with **ALK-660** will defat the skin. Avoid skin contact through the use of rubber gloves.

---

**Notice:** The information presented here is based upon our laboratory tests and field use experience. Since conditions of actual use are beyond our control, any recommendations or suggestions are made without warranty, express or implied. **Eldorado Chemical Co., Inc.**'s sole obligation shall be to replace that portion of the product shown to be defective; nor shall we be liable for any loss, damage or injury—direct or consequential—arising out of the use of this product.

Rev. 041703

**Eldorado Solutions, Inc.** (dba of Eldorado Chemical Co, Inc.) 8935 N. Meridian Ste 205 Indianapolis, IN 46260  
Manufacturing: San Antonio, TX [www.eldoradochem.com](http://www.eldoradochem.com) [techservice@eldoradochem.com](mailto:techservice@eldoradochem.com) (800) 531-1088