



PRODUCT BULLETIN

1200 Label and Adhesive Remover

Rev.Date 10-1-04
page 1 of 2

General Description

DoradoZolve™ 1200 Label and Adhesive Remover will quickly soften and remove carpet underlayment, black mastic, and a wide variety of acrylic, asphalt and latex glues. By reducing labor of adhesive removal, **DoradoZolve™ 1200** makes commercial and residential flooring restorations cost effective and easy.

Features and benefits

- Non Abrasive
- Water rinse clean up
- Easy to Use
- No petroleum solvents
- Clings to vertical surfaces.
- Safe on most paints
- Penetrating liquid formulation

Recommended Usage

- Foam Carpet Underlay
- Indoor/ Outdoor Carpet
- Tile Adhesive
- Black Mastic
- Flooring & Laminate adhesive
- Tape & Sticker residue
- Bubble gum

Product Data

- Viscosity: <200 cps
- Appearance: Clear Thin Liquid
- Specific Gravity: 0.85
- Boiling Point: > 300°F
- Freezing Point: 14°F
- pH: N/A
- Flash Point: >120°F
- Coverage: 20-125 sq. ft/gal. (Theoretical)
- VOC (EPA Method 24): 810 g/L
- Shelf Life: 24 months

Safety requirements

Do not use in confined spaces. Avoid contact with skin, eyes, and clothing. Avoid contact of fumes with ignition sources. If ingested, call a physician or poison control center immediately. Do not induce vomiting, give glass of citrus juice or milk. If contacted to skin or eyes, flush thoroughly with water for 15 minutes.

Do not use in confined spaces. Avoid skin contact through the use of rubber gloves. Avoid contact of fumes with ignition sources.

DoradoZolve™ 1200 is combustible.

Proper safety procedures should be followed at all times while handling this product. Refer to the Material Safety Data Sheet for important health/safety information before use.

Limits On Use

Surface temperatures should be between 32°F to 120°F

Directions for use

- 1) **Test Area:** Always prepare a test area prior to full application. 1200 can effect floor finishes and project surfaces. Some subfloors are moisture sensitive and may not be suitable for water rinse.
- 2) **Mixing:** Do not dilute, product is packaged ready to use.
- 3) **Removal** all loose carpet foam, underpad. Expose all areas of adhesive to be removed.



PRODUCT BULLETIN

1200 Label and Adhesive Remover

Rev.Date 10-1-04
page 2 of 2

4) Application: Carpet & Vinyl Adhesive:

Apply **DoradoZolve™ 1200** to the surface using a roller, brush, mop or rag. Allow dwell time of 15 to 30 minutes or until glue has softened. Ensure that sufficient product has been applied to thoroughly saturate the remaining under pad or glue residue. Underpad stuck to flooring with soften and can removed with a scrapper. Repeat procedure for stubborn areas. When removing linoleum or tile, pre-cut the surface into approximately 2-inch squares to allow the product to penetrate to the glue beneath.

minute additional contact time. Then, place hot water in the clean water tank and use the solution/scrub/vacuum option to lift off the dissolved mastic. A de-foaming agent should be introduced into the wastewater tank to prevent overflow.

Packaging

1 gal (3.8 L)
5 gal (19.0L)
55 gal (210 L)

5) Application: Black tile mastics: Pour

DoradoZolve™ 1200 to the surface and spread using 36" wide bristle brooms. Let 1200 dwell for 45 to 120 minutes. Agitate periodically to working in remover, and test progress. Contact time is dependent on temperature, humidity and thickness of mastic. Once mastic is easily be moved, begin removal.

6) Removal:

Remove the residue with scrappers, squeegees, or stiff bristle brushes. Rinse with detergent and water after removal and allow to dry. Floor Scrubbing Equipment: If floor-scrubbing equipment are employed, equip the scrubber with synthetic bristle or wire brushes are preferred. Pad brushes verses cylindrical brushes are also preferred. Apply the product and agitate mastic twice using the scrubber. Allow an additional 30 minutes contact time and remove. Riding Floor Scrubbing Equipment: Agitate twice and allow 30-