



PRODUCT BULLETIN

ELDORADO PC-1020 PROTECTIVE COATING

ELDORADO PC-1020 is a temporary, transparent water-based soil barrier applied to hard surfaces to protect paint, metals, and plastics from corrosion and to prevent soils, such as exhaust soot from becoming attached to clean surfaces. *PC-1020* is easily removed and reapplied.

PROPERTIES

1. Produces a glossy, hard, clear, and colorless coating.
2. Prevents temporary corrosion of metals.
3. Prevents oxidation and dulling of painted surfaces.
4. Safe on paint, electrical insulation, Plexiglas,TM and other plastics.
5. Dries rapidly.
6. Prevents soils from penetrating paint or from corroding metals.
7. Water resistant.
8. Contains no regulated materials which would cause disposal problems.
9. Nontoxic and non-flammable.

USE

Apply *PC-1020* to clean surfaces by brush, roller, mop, or spray. Surfaces need not be dry since *PC-1020* is water-soluble. Thinning may be accomplished by adding water, if necessary. Rough surfaces may require 2 coats; allow 20 to 60 minutes' drying time between coats.

A full day is required for maximum water resistance of the coating.

Removal: Apply **Eldorado Astromat A** by spray, brush, or mop to the surface; allow to dwell for 10 to 30 minutes; agitate with a brush, then rinse off with water.

PRECAUTIONS

Avoid prolonged skin contact with *PC-1020* solutions. Consult MSDS for further details.

Eldorado Solutions, Inc. (dba of Eldorado Chemical Co, Inc.) 8935 N. Meridian Ste 205 Indianapolis, IN 46260
Manufacturing: San Antonio, Miami www.eldoradochem.com techservice@eldoradochem.com (800) 531-1088

NOTICE: The information presented here is based upon our laboratory tests and field use experience. Since conditions of actual use are beyond our control, any recommendations or suggestions are made without warranty, express or implied. **Eldorado Chemical Co., Inc.**'s sole obligation shall be to replace that portion of the product shown to be defective; nor shall we be liable for any loss, damage or injury—direct or consequential—arising out of the use of this product.

Rev. 041503

