



PRODUCT BULLETIN

ELDORADO PR-3700 PAINT REMOVER

ELDORADO PR-3700 is a viscous, nonphenolic, nonchromate, low-odor paint remover, particularly effective for removal of aircraft finishes.

PROPERTIES

1. Effective for removal of acrylic, epoxy, and polyurethane paints.
2. Nonflammable
3. Contains no chromates or heavy metals.
4. Safe on aluminum, cadmium, magnesium, and ferrous alloys.
5. Approved by or conforms to: Boeing D6, AMS 1375

USE

Spray or brush ***PR-3700*** onto surface to be stripped. Allow 30 minutes to 1 hour for paint to be loosened. Agitate to break remaining bond, then squeegee paint and stripper residues from the surface.

Conditions of humidity and temperature will dictate dwell time. ***PR-3700*** should remain in contact with the paint for as long as possible without drying. Clean stripped surface with a good cleaner to remove all stripper residues.

PRECAUTIONS

Avoid all skin contact. ***PR-3700*** contains methylene chloride and must be used with adequate ventilation. **Do not use in confined spaces.**

When application is made on a large-scale, full wash rack gear—consisting of rubber boots, gloves, face mask, and rubber clothing—should be worn to avoid contact of material with skin. If skin contact occurs, wash immediately with soap and water.

Eldorado Solutions, Inc. (dba of Eldorado Chemical Co, Inc.) 8935 N. Meridian Ste 205 Indianapolis, IN 46260
Manufacturing: San Antonio, Miami www.eldoradochem.com techservice@eldoradochem.com (800) 531-1088

NOTICE: The information presented here is based upon our laboratory tests and field use experience. Since conditions of actual use are beyond our control, any recommendations or suggestions are made without warranty, express or implied. **Eldorado Chemical Co., Inc.**'s sole obligation shall be to replace that portion of the product shown to be defective; nor shall we be liable for any loss, damage or injury—direct or consequential—arising out of the use of this product.

Rev. 041503

