



PRODUCT BULLETIN

ELDORADO POLISH XM ALUMINUM METAL POLISH

ELDORADO POLISH XM is a viscous polish for aluminum surfaces. The abrasive nature of ***Polish XM*** enables it to remove tarnish and to produce a high-lasting polish on unpainted clad, aluminum surfaces. ***Polish XM*** is designed to be used for spot polishing or with power buffing equipment.

PROPERTIES

1. Opaque, viscous liquid.
2. Flash Point: Above 190°F.
3. Safe on aluminum alloys.
4. Mild odor; reduces worker fatigue.
5. Approved by or conforms to: AMS 1650; MIL-P-6888.

USE

Apply ***Polish XM*** to the surface to be polished, or apply on the polish buffer pad. Buff the surface approximately 1 minute. Allow residues to dry. Buff with clean pads to remove residues and to achieve the desired finish. After polishing, apply a suitable solvent-type aircraft wax to protect the surface. Removal of oxides, prior to buffing, with **Eldorado AC-6** will reduce buffing time.

PRECAUTIONS

Contains petroleum solvent and abrasive. A dust mask is required to avoid breathing abrasive particles. Avoid contact with skin and eyes through the use of rubber gloves and goggles. **Do not use in confined spaces.** In case of accidental contact with eyes, flush with plenty of water and contact physician. If accidentally ingested, seek medical attention.

Eldorado Solutions, Inc. (dba of Eldorado Chemical Co, Inc.) 8935 N. Meridian Ste 205 Indianapolis, IN 46260
Manufacturing: San Antonio, Miami www.eldoradochem.com techservice@eldoradochem.com (800) 531-1088

NOTICE: The information presented here is based upon our laboratory tests and field use experience. Since conditions of actual use are beyond our control, any recommendations or suggestions are made without warranty, express or implied. **Eldorado Chemical Co., Inc.**'s sole obligation shall be to replace that portion of the product shown to be defective; nor shall we be liable for any loss, damage or injury—direct or consequential—arising out of the use of this product.

Rev.041503

